

SCREAMER 4 - 040-EZ-99

(January 2023)

P.n.: CZ3N00100UC

Technical Data:

Class:	KZ/KZ2
Design:	Single cylinder – 2 stroke
Displacement:	124.59cc
Bore:	Ø 54.00 mm
Max. Bore:	Ø 54.08 mm
Stroke:	54.40 mm
Inlet System:	Reed valve
Lubrication:	Oil mixture
Ignition System:	Analogical
Transmission:	6 Speed
Cooling System:	Water cooled
Starter:	Push start
Carb. Model:	Dell'Orto VSH30CS
Max. Power:	N.D.
Max. Torque:	N.D.
Max. Rpm Limit:	No limiter



Main Features:

Dual part cylinder head assembly - Nikasil cylinder - Reed group housed in crankcase - 4 reed petals group - Water cooled crankcase, cylinder and head - Primary pair with straight rectified toothing - Multi-plate dry clutch with shock absorber - Clutch thrust plate with thrust bearing - Homologated 6 speed gearbox - Gears on roller cages - Feed lubrication on primary shaft - Lightened selector drum - Shifty forks with case hardened and tempered shoes - Lightened primary gear - CNC reed group conveyor - Main roller bearings - Factory combustion chamber and piston - Resin conveyor - Factory exhaust manifold - Factory carburettor setup

Accessories:

Homologated Ø 58mm rotor electronic analogic ignition - H.T. coil with damping spacers - NGK BR 10 EG spark plug - Spark plug cap - Dell'Orto VSH30CS carb. - Carburettor manifold - Mikuni fuel pump with support plate - Z17 sprocket - Exhaust manifold with fixing springs - Homologated exhaust muffler/tail pipe - Magnesium engine mount